

AERIAL SPLICING TRAILER (AST)



SPACIOUS 8' X 10' SPLICING LAB

Design

Self-contained equipment package
DC Powered Aerial Charged by
Generator Security on the Job

Environmentally Responsible

No truck engine idle
Echo throttle generator
Reduces fuel consumption
Reduces noise pollution
CARB compliant



AERIAL SPECIFICATIONS

25' 6" HORIZONTAL SIDE REACH
38' 4" HEIGHT BOTTOM BASKET
43' 4" WORKING HEIGHT
12' 3" STOWED HEIGHT
350 LBS BASKET CAPACITY
540 DEGREE ROTATION
24 VDC POWER AERIAL
ELECTRIC TOOL OUTLET AT BASKET
EMERGENCY LOWER 12 VDC
PROPORTIONAL UPPER CONTROLS W/ SINGLE
HANDLE ACTUATOR
SIDE MOUNTED WALK-THRU BASKET W/DOOR
LIGHTWEIGHT ALUMINUM INNER BOOM
HYDRAULIC LEVELING BASKET
PEDESTAL RISER HOUSES HYDRAULIC RESERVOIR
AND BATTERIES
UTLN41 MEETS AND EXCEEDS ANSI A92.9-2015 &
OSHA REQUIREMENTS

SPLICING LAB

6' 2" INTERIOR BODY HEIGHT
505 CU/FT OF USEABLE CARGO SPACE
FULL SERVICE MOBILE WORKSHOP
INSULATION IN WALLS & FLOOR
AC & HEAT
FULL LENGTH SPLICING TABLE
2 SPLICING DOORS
FULL HEIGHT DRAWER SET
CABINET STORAGE
DOT LIGHTING
AMBER STROBES
EXTERIOR WORK LIGHTS

TRAILER SPECIFICATIONS:

10,000 LBS GVWR
8,960 LBS TRAILER WEIGHT
1,040 LBS TRAILER PAYLOAD
13' TRAILER LENGTH
1,500 LBS TONGUE WEIGHT



THE CONNER GROUP, LLC

113 Ennis St, Unit A, Saraland, AL 36571

office: 251-725-0130

cell: 470-755-9797

email: chris@tcgequip.com

<https://tcgequip.com>

