THE CONNER GROUP

TAYLOR TM50

DIESEL GENERATOR

EQUIPMENT RENTALS

3-PHASE PRIME	FUEL	FREQUENCY	ENGINE SPEED
39 kW	Diesel	60 Hz	1,800 RPM



Representative composite image. Actual rental equipment may vary.

PACKAGE HIGHLIGHTS

- Kohler KDI2504TCR diesel engine
- EPA Tier 4 Final
- Leroy Somer LSA42.3M7 alternator
- DeepSea 7310 controller
- Integral 71 gallons fuel tank
- Multiple voltage output options
- D350 regulator; ±0.25% regulation
- Cellular gateway for remote monitoring
- External fuel tank connections
- Cam-Lok and busbar output connections

PRIME OUTPUT POWER OPTIONS

Voltage	Phase	kW / kVA	Amps
277/480	3	39/49	59
120/208	3	39/49	135
120/240	3	39/49	117
120/240	1	30/30	125

TRAILER-MOUNTED DIESEL GENERATOR

Rental availability and rates: contact THE CONNER GROUP.

TAYLOR TM50 GENERATOR

TECHNICAL & COMPONENT DETAILS

ENGINE DATA

Manufacturer	Kohler
Model	KDI2504TCR
EPA Tier	4 Final
Aspiration	Turbocharged
Arrangement	Inline 4 Cylinder
Displacement: L (in.³)	2.482 (151.46)
Gross Horsepower	63.1
Rated RPM	1800
Block Heater Wattage	500

DIMENSIONS & WEIGHT

Length: in.	160
Width: in.	74
Height: in.	75
Wet Weight: lbs	4573

FUEL SYSTEM

Fuel Type	Ultra-Low Sulfur Diesel
Fuel Capacity: gal	71
Containment	110%
Consumption @ 75% Load: gal/hr	2.17
Consumption @ 100% Load: gal/hr	2.89

DEF & SOUND LEVEL

DEF Capacity: gal	N/A
Sound Level at 23 Feet: dBA	69

OUTPUT CONNECTIONS

20A 120V Receptacles	2
50A 120-240V Receptacles	3
Cam-Lok Sets	1

