TRACK LOADER

KATO CL35

COMPACT TRACK LOADER

DUMPING HEIGHT	RATED OUTPUT	RATED CAPACITY 35%	AUXILIARY FLOW
7 ft 9 in	62 hp	1,720.7 lb	17 gpm



Supplied equipment photo; rental unit and installed attachments may vary.

LIFTING & BUCKET

Max. operating height	12 ft 9 in
Max. hinge-pin height	9 ft 11 in
Tipping capacity	4,916.3 lb
Capacity at 50% tip	2,458.2 lb
Heaped bucket capacity	12.7 cu ft
Bucket width	5 ft 8 in

PERFORMANCE & CONFIGURATION

Engine	Kubota V2403-CR diesel
Operating weight	7,804.4 / 7,936.6 lb
Transport weight	7,639.0 / 7,771.3 lb
Travel speed, low/high	4.2 / 6.2 mph
Gradeability	30 degrees
Ground psi, canopy/cab	5.62 / 5.71 psi
Bucket digging force	6,474 lb
Fuel capacity	24 gal
Hydraulic pressure	2,987.8 psi
Hydraulic tank capacity	10.6 gal

ATTACHMENT APPLICATIONS

17 gpm auxiliary hydraulic flow.

Photo shows a grapple attachment.

Manufacturer ratings vary by configuration; confirm rental unit and supplied attachment.
Source: KATO CL35 specification sheet and katoces.com/product/cl35-track-loader/.