THE CONNER GROUP

SKID STEER

KATO AS12

RUBBER-TIRE LOADER

DUMPING HEIGHT	RATED OUTPUT	OPERATING WEIGHT	SAE LOAD CAPACITY
6 ft 8 in	21 hp	2,955 lb	728 lb



Supplied equipment photo; rental unit and installed attachments may vary.

DIMENSIONS & REACH

Operating height, raised	10 ft 10 in
Hinge-pin height, raised	8 ft 4 in
Dumping height	6 ft 8 in
Total length	8 ft 6 in
Ground clearance	6 in
Rubber tire size	23 x 8.50-12

PERFORMANCE & CONFIGURATION

Engine	Yanmar 3TNV76 diesel
Rated engine speed	2,500 rpm
Transport weight	2,778 lb
Maximum travel speed	4.35 mph
Bucket breakout force	1,658 lb
Auxiliary flow	7.4 gpm
Hydraulic pressure	2,610 psi
Battery	12 V
Cooling system	Water cooled
Controls	Pilot-operated joysticks

COMPACT MATERIAL HANDLING

Pilot-operated joystick controls.

7.4 gpm auxiliary hydraulic flow.

Manufacturer model specifications; confirm the rental unit, load rating and attachments.
Source: KATO AS12 specification sheet and katoces.com/product/as12-skid-steer/.