WHEEL LOADER

HYUNDAI HL930A

STANDARD Z-BAR

NET ENGINE POWER	HEAPED BUCKET	OPERATING WEIGHT	BUCKET BREAKOUT
130 hp	2.50 yd³	25,595 lb	20,175 lbf



Illustrative jobsite composite. Actual equipment condition and rental configuration may differ.

REFERENCE DIMENSIONS

Dump clearance at 45°	8 ft 10 in
Dump reach at 45°	3 ft 6 in
Hinge pin at max. lift	11 ft 11 in
Wheelbase	9 ft 6 in
Width over tires	7 ft 10 in
Cab height	10 ft 5 in

PERFORMANCE & CONFIGURATION

Engine	Cummins B4.5, 4-cylinder diesel
Rated speed / emissions	2,200 rpm / Tier 4 Final
Drive system	Four-wheel drive
Transmission	Automatic powershift, F4 / R3
Hydraulic system	Load sensing
Hydraulic pump flow	34.9 gpm
Max. forward speed	24.9 mph
Fuel / DEF capacity	50.0 gal / 5.0 gal
Ground clearance	15 in
Steering angle	40° left / 40° right

STANDARD Z-BAR REFERENCE

2.50 yd³ pin-on bucket with cutting edge.

Couplers and XT versions change specs.

Manufacturer reference ratings and approximate dimensions. Confirm unit, bucket, coupler and options.
Source: HD Hyundai North America HL930A specification sheet, pp. 2-3 (linked).