MULCHING ATTACHMENT

FECON RK6015

STANDARD FLOW HEAD

WORKING WIDTH	ATTACHMENT WEIGHT	CUTTING TOOLS	ROTOR DIAMETER
60 in	1,465 lb	26	15 in



Supplied photo shown unchanged. Specifications apply to the mulching head, not the carrier.

APPLICATIONS & SETUP

- Brush and vegetation management
- Fence rows and crop perimeters
- Property and land cleanup

CARRIER FITMENT

For compatible skid steers and compact track loaders. Verify lift capacity, mount, hoses, couplers and hydraulic settings.

OPERATOR PROTECTION

Use an approved enclosed cab with 1/2 in polycarbonate guarding and follow the attachment and carrier manuals.

PERFORMANCE & CONFIGURATION

Overall width	71 in
Rotor speed	2,400 rpm
Rotor design	Split ring
Hydraulic motor	45 cc variable displacement
Maximum pressure	4,000 psi
Maximum carrier power	75 hp
Material diameter	Up to 5 in
Hydraulic flow	Confirm for specific unit
Push bar	Adjustable, bolt-on
Service access	Hinged motor cover

Flow ratings differ across Fecon publications. Confirm unit-specific hydraulic requirements before pairing.
Sources: Fecon Standard Flow product page and SFR_022022 brochure. Ratings vary with setup and conditions.