LONG REACH EXCAVATOR

HYUNDAI HX300LR

CRAWLER EXCAVATOR

MAX. DIGGING REACH	MAX. DIGGING DEPTH	NET ENGINE POWER	OPERATING WEIGHT*
60 ft 9 in	48 ft 7 in	230 hp	72,910 lb



Illustrative jobsite composite. Actual equipment condition and rental configuration may differ.

WORKING RANGES

Reach at ground level	60 ft 4 in
Maximum digging height	47 ft 7 in
Maximum dumping height	40 ft 0 in
Vertical wall digging depth	39 ft 5 in
Minimum swing radius	20 ft 6 in
Bucket capacity (SAE)	0.68 cu yd

PERFORMANCE & CONFIGURATION

Engine	Cummins QSB6.7 diesel
Net power (SAE J1349)	230 hp at 1,950 rpm
Emissions reference	Tier 4 Final
Overall length	47 ft 9 in
Width with 800 mm shoes	11 ft 2 in
Overall boom height	11 ft 8 in
Travel speed, low/high	2.05 / 3.67 mph
Maximum swing speed	10.2 rpm
Bucket digging force, SAE	15,650 lbf
Fuel tank capacity	132 US gal

PUBLISHED REFERENCE SETUP

10.2 m boom / 7.85 m arm; 800 mm shoes.

*Approximate weight with standard bucket.

Reference data only. Verify the unit, boom, arm, bucket, counterweight and lift chart before use.
Source: Hyundai HX300LR manufacturer specifications, publication 1072-EX-SP.