THE CONNER GROUP
AUGERS / BUCKETS / HD DRILLS / SPLICING / COW

WOMEN-OWNED
UTILITY BUSINESS

NEW EQUIPMENT SALES

# RAM 5500 / VERSALIFT VST-40-MHI

## INSULATED BUCKET TRUCK | 4x4 DIESEL | MATERIAL HANDLER




**WORKING HEIGHT**
**45 ft 4 in**

**SIDE REACH**
**30.17 ft**

**PLATFORM CAPACITY**
**500 lb**

**MATERIAL HANDLING**
**1,000 lb**

### AERIAL ACCESS AND ORGANIZED UTILITY STORAGE

AERIAL PACKAGE

46 kV boom insulation
Continuous unrestricted rotation
24 x 30 x 42-in closed fiberglass platform
Platform liner and cover
4-axis upper controls / turret lower controls
Hydraulic tool outlets at platform
Modified A-frame front outriggers

CHASSIS & BODY

RAM 5500 standard cab / 4x4
Cummins 6.7L I6 diesel / 360 hp
8-speed automatic / 19,500-lb GVWR
Hydraulic brakes / 52-gal fuel tank
132-in Load King steel line body
Adjustable shelves and material hooks
Rear-access hotstick shelf
10-ton pintle/ball combination hitch

Final configuration, availability, taxes and delivery confirmed with quotation.

## CALL FOR PRICE

# VST-40-MHI PACKAGE DETAILS

**BOOM | CONTROLS | BODY | CHASSIS & SAFETY**

## BOOM & CONTROLS

Fiberglass upper boom
Steel and fiberglass lower boom
Upper articulation: -25 to 85 degrees
Lower articulation: 0 to 87 degrees
Open-center hydraulics
Auxiliary hydraulic let-down with controls
Engine start/stop and throttle advance

## BODY & TOWING

132-in white steel line body
Anti-skid tops, bed, tail shelf, cargo walls
Curbside and rear body access
Wheel-chock and outrigger storage
Level indicators and outrigger interlock
7-way RV blade trailer receptacle
Trailer brake controller
Front and rear tow hooks

## CHASSIS & RUNNING GEAR

7,000-lb front axle
13,500-lb rear axle
225/70R19.5 tires / steel wheels
4.44 rear axle ratio
Limited-slip differential

## CAB & SAFETY EQUIPMENT

Heated mirrors
Power locks and windows
40/20/40 vinyl split-bench seat
Rear camera and backup alarm
Beacon strobe
Fire extinguisher and first-aid kit

**CALL FOR PRICE**