THE CONNER GROUP

WOMEN-OWNED UTILITY BUSINESS

NEW EQUIPMENT SALES

DUR-A-LIFT DPM2-40DP

AERIAL EQUIPMENT | CONFIGURATION-SPECIFIC SALES SHEET



PACKAGE AT A GLANCE

HEIGHT TO PLATFORM BOTTOM
40 ft

MAXIMUM WORKING HEIGHT*
47 ft

SIDE REACH
30 ft 3 in

BASKET CAPACITY
600 lb

FEATURES & SPECIFICATIONS

- Height to platform bottom: 40 ft
- Maximum working height*: 47 ft
- Side reach: 30 ft 3 in
- Approx. stowed height: 10 ft 6 in
- Approx. lift weight: 3,800 lb
- Articulating arm travel: 0 to 83 deg
- Main boom travel: -29 to 70 deg
- Extension travel: 96 in
- Basket capacity (DP): 600 lb
- Basket rotation: 180 degrees
- Basket: 24 x 42 in; aluminum or fiberglass
- Lift: Double-person telescopic articulating
- Leveling / controls: Hydraulic leveling; proportional; lower override
- Basket functions: Engine start/stop; ground-level access
- Insulation: DPM2: Category C or D; DPM2S: non-insulated
- Available options: Elevator, outriggers, liners, tool circuits, DC backup

Maximum working height requires optional 22-in basket elevator. Confirm quoted chassis, insulation category and installed options. Approximate weights/heights vary by build.

EQUIPMENT SALE PRICE

Configuration, availability and applicable tax/delivery confirmed on quotation.

CALL FOR PRICE