THE CONNER GROUP

WOMEN-OWNED UTILITY BUSINESS

NEW EQUIPMENT SALES

DUR-A-LIFT DPM-47 MH-DU

AERIAL EQUIPMENT | CONFIGURATION-SPECIFIC SALES SHEET



PACKAGE AT A GLANCE

WORKING HEIGHT
52 ft

SIDE REACH
31 ft 6 in

JIB / WINCH
Up to 1,000 lb

BASKET MODES
MH / DU configurations

FEATURES & SPECIFICATIONS

- Working height: 52 ft
- Platform height: 47 ft
- Side reach: 31 ft 6 in
- Mh basket: 24 x 30 in; single-person; 400 lb
- Du basket: 24 x 42 in; 400 lb with jib; 550 lb without jib in personnel mode
- Side mounted jib winch: Up to 1,000 lb; follow unit load chart
- Approx stowed travel height: 10 ft 5 in
- Approx lift weight: 4,300 lb
- Articulating arm travel: 0 to 75 degrees
- Main boom travel: -30 to 75 degrees
- Extension travel: 120 in
- Minimum chassis gvwr: 19,500 lb
- Minimum cab to axle: 84 in
- Aerial rotation: Continuous
- Basket leveling: Hydraulic
- Controls: Proportional; lower override; engine start/stop from basket

MH basket rotation: 180 degrees. DU: 100 degrees standard / 180 optional per literature; webpage differs. DPM insulated Category C or D; DPMS non-insulated. Confirm quoted configuration and follow unit load chart.

EQUIPMENT SALE PRICE

Configuration, availability and applicable tax/delivery confirmed on quotation.

CALL FOR PRICE