# FREIGHTLINER M2106 / TEREX COMMANDER 6060

**NEW 60-FT DIGGER DERRICK PACKAGE | READY TO BUILD YOUR FLEET**




## PERFORMANCE

**MAX SHEAVE HEIGHT**
**60 ft**

**MAX LIFT CAPACITY**
**30,000 lb**

**CAPACITY @ 10 FT**
**18,100 lb**

**MAX LOAD RADIUS**
**50.3 ft**

**MEDIAN DIG RADIUS**
**26.9 ft**

**TURNTABLE WINCH**
**15,000 lb**

## PACKAGE HIGHLIGHTS

- Terex Commander 6060 with continuous unrestricted rotation
- Dual lift cylinders with +80° to -20° boom articulation
- 24 in. TXC carbide-tooth auger with 2-5/8 in. kelly bar
- Heavy-duty A-frame front outriggers and radial rear outriggers
- Freightliner M2106 6x6 chassis with Cummins L9 diesel
- 360 HP with Allison 3000 RDS automatic transmission
- 58,000 lb GVWR with tandem rear axle configuration
- Custom 180 in. steel T-style flatbed with material storage

## CHASSIS PACKAGE

**Freightliner M2106 | 6x6 | Cummins L9 Diesel | Allison 3000 RDS Automatic**

58,000 lb GVWR | Air brakes | 18,000 lb front axle | 40,000 lb tandem rear axle

**NEW EQUIPMENT PACKAGE PRICE**

PLUS TAX & DELIVERY (WHERE APPLICABLE)

**CALL FOR PRICE**

# COMMANDER 6060 TECHNICAL DETAILS

## DIGGER-DERRICK PERFORMANCE, CHASSIS AND STANDARD EQUIPMENT




### DIGGER DERRICK SPECS

| | |
|---|---|
| ROTATION | Continuous unrestricted |
| MAX LIFT CAPACITY | 30,000 lb |
| CAPACITY @ 10 FT | 18,100 lb |
| MAX SHEAVE HEIGHT | 60 ft |
| MAX LOAD RADIUS | 50.3 ft |
| MEDIAN DIG RADIUS | 26.9 ft |
| CAPACITY @ MEDIAN | 3,194 lb |
| HYDRAULIC RESERVOIR | 50 gal |

## CHASSIS & DRIVETRAIN

- Freightliner M2106 conventional cab, 6x6 configuration
- Cummins L9 diesel engine, 360 horsepower
- Allison 3000 RDS automatic transmission
- Meritor MX-18-120HR 18,000 lb front axle
- Meritor MT-40-14X 40,000 lb tandem rear axle
- Air rear suspension; 58,000 lb GVWR; 6.14 rear axle ratio
- 50-gallon fuel tank and 6-gallon DEF tank

## BOOM, CONTROLS & OUTRIGGERS

- Steel main and intermediate booms with rectangular filament-wound fiberglass third stage
- Single-stick T-handle main controls with full-pressure, open-center hydraulics
- Right-hand command post with engine start/stop and foot throttle
- Heavy-duty A-frame front outriggers; radial rear outriggers; four outrigger pads included
- 15,000 lb turntable winch; 24 in. TXC carbide-tooth auger; 2-5/8 in. kelly bar
- Meets or exceeds ANSI A10.31 standards

## BODY & TOWING

180 in. steel T-style flatbed | T-box shelves/material hooks | Wheel-chock storage | Anti-skid bed space | 30-ton pintle hitch | 7-way RV receptacle | Front tow hooks and rear D-rings | 0.5 in. x 50 ft twin hydraulic hose reel | Pole carrier

**BUILT FOR TRANSMISSION & HEAVY UTILITY WORK**

Configured for demanding pole-setting, digging and lifting applications.