THE CONNER GROUP

WOMEN-OWNED UTILITY BUSINESS

NEW EQUIPMENT SALES

KATO AS12

RUBBER-TIRE LOADER | EQUIPMENT SALES



MODEL AT A GLANCE

DUMPING HEIGHT
6 ft 8 in

RATED OUTPUT
21 hp

OPERATING WEIGHT
2,955 lb

SAE LOAD CAPACITY
728 lb

DIMENSIONS & REACH

Operating height, raised	10 ft 10 in
Hinge-pin height, raised	8 ft 4 in
Dumping height	6 ft 8 in
Total length	8 ft 6 in
Ground clearance	6 in
Rubber tire size	23 x 8.50-12

COMPACT MATERIAL HANDLING

Pilot-operated joystick controls.

7.4 gpm auxiliary hydraulic flow.

PERFORMANCE & CONFIGURATION

Engine	Yanmar 3TNV76 diesel
Rated engine speed	2,500 rpm
Transport weight	2,778 lb
Maximum travel speed	4.35 mph
Bucket breakout force	1,658 lb
Auxiliary flow	7.4 gpm
Hydraulic pressure	2,610 psi
Battery	12 V
Cooling system	Water cooled
Controls	Pilot-operated joysticks

Manufacturer model specifications; confirm the quoted unit, load rating and attachments.

EQUIPMENT SALES

Contact The Conner Group for configuration, options and availability.

CALL FOR PRICE