THE CONNER GROUP

WOMEN-OWNED UTILITY BUSINESS

NEW EQUIPMENT SALES

DUR-A-LIFT DPM-52 MH-DU

MATERIAL HANDLER | CONFIGURATION-SPECIFIC SALES SHEET



PERFORMANCE

WORKING HEIGHT
57 ft

PLATFORM HEIGHT
52 ft

SIDE REACH
31 ft 6 in

JIB / WINCH
Up to 1,000 lb

BASKET MODES
MH / DU configurations

FEATURES & SPECIFICATIONS

MH basket: 24 x 30 in; single-person; 400 lb

DU basket: 24 x 42 in; 400 lb with jib; 550 lb without jib in personnel mode

Side-mounted jib winch: Up to 1,000 lb; follow unit load chart

Approx. stowed travel height: 11 ft 8 in

Approx. lift weight: 4,400 lb

Articulating arm travel: 0 to 75 degrees

Main boom travel: -30 to 75 degrees

Extension travel: 120 in

Aerial rotation: Continuous

Basket leveling: Hydraulic

Controls: Proportional; lower override; engine start/stop from basket

MH basket rotation: 180 degrees. DU: 100 degrees standard / 180 optional per literature; webpage differs. DPM insulated Category C or D; DPMS non-insulated. Confirm quoted configuration and follow unit load chart.

MINIMUM CHASSIS REQUIREMENTS

22,000 lb GVWR | 108 in cab-to-axle (CA)

CUSTOMER-SELECTABLE REFERENCE: FREIGHTLINER M2 106 PLUS

4x4 standard cab | Cummins L9 diesel, 300 hp | Allison 3000 RDS-P | 33,000 lb GVWR

Reference package, not a required chassis. Final compatibility and configuration confirmed on quotation.

EQUIPMENT SALE PRICE

Configuration, availability and applicable tax/delivery confirmed on quotation.

CALL FOR PRICE