THE CONNER GROUP

WOMEN-OWNED UTILITY BUSINESS

NEW EQUIPMENT SALES

DUR-A-LIFT DLT2-60DU TRUCK

AERIAL EQUIPMENT | CONFIGURATION-SPECIFIC SALES SHEET



PACKAGE AT A GLANCE

MAXIMUM WORKING HEIGHT*
67 ft

SIDE REACH
39 ft 2 in

TOP-MOUNTED JIB/WINCH
Up to 1,000 lb

BASKET ROTATION
180 degrees

FEATURES & SPECIFICATIONS

Chassis: Freightliner M2 106
Service body: 150-in BrandFX body
Basket: 24 x 42 in DU fiberglass
Basket capacity: 400 lb with winch; 550 lb without winch
Aerial rotation: Continuous
Controls: Proportional; lower override
Leveling: Hydraulic
Engine control: Start/stop from basket
Basket elevator: 22 in; required for stated working height
Basket access: From ground
Stowed travel height: Approx. 12 ft
Insulation: Category C reference build

OPTIONAL / REFERENCE CHASSIS PACKAGE

Freightliner M2 106 Plus | 4x4 standard cab | Cummins L9 diesel, 300 hp

Allison 3000 RDS-P automatic | 33,000 lb GVWR reference only

Optional chassis reference, not a confirmed supplied build. Confirm actual chassis and final configuration.

*67-ft maximum working height requires the optional 22-in basket elevator. Chassis/body match, insulation category and final options confirmed on sales order. Follow unit load chart.

EQUIPMENT SALE PRICE

Configuration, availability and applicable tax/delivery confirmed on quotation.

CALL FOR PRICE