THE CONNER GROUP

WOMEN OWNED
UTILITY BUSINESS
EQUIPMENT SALES

TAYLOR TM50 GENERATOR

39 kW THREE-PHASE PRIME | TRAILER-MOUNTED DIESEL GENERATOR



POWER & PERFORMANCE

ENGINE
Kohler KDI2504TCR

FUEL CAPACITY
71 gallons

FREQUENCY
60 Hz

ENGINE SPEED
1,800 RPM

PORTABLE DIESEL POWER. READY FOR THE JOBSITE.

Trailer-mounted power with a turbocharged, EPA Tier 4 Final diesel engine.
Multiple voltage options, integral fuel tank and convenient output connections.

PACKAGE HIGHLIGHTS

- Leroy Somer LSA42.3M7 alternator
- D350 regulator; ±0.25% regulation
- Cellular gateway for remote monitoring
- Deep Sea 7310 controller
- External fuel tank connections
- Cam-Lok and busbar output connections

OUTPUT POWER OPTIONS

Genset	Voltage	Alternator	Model	Phase	Reg.	Regulation	Hz	kW/kVA	Amps
TM50	277/480	Leroy Somer	LSA42.3M7	3	D350	±0.25%	60	39/49	59
	120/208		LSA42.3M7	3	D350	±0.25%	60	39/49	135
	120/240		LSA42.3M7	3	D350	±0.25%	60	39/49	117
	120/240		LSA42.3M7	1	D350	±0.25%	60	30/30	125

Output ratings reproduced from the supplied TM50 specification sheet.

CALL FOR PRICE

Specifications/options vary; confirm quoted configuration.

TAYLOR TM50 GENERATOR

TECHNICAL SPECIFICATIONS & COMPONENT DETAILS

Engine Data	TM50
Manufacturer	Kohler
Model	KDI2504TCR
EPA Tier	4 Final
Aspiration	Turbocharged
Arrangement	Inline 4 Cylinder
Displacement: L (in.^{3})	2.482 (151.46)
Gross Horsepower	63.1
Rated RPM	1800
Block Heater Wattage	500

Dimensions & Weight	
Length: in.	160
Width: in.	74
Height: in.	75
Wet Weight: lbs	4573

Fuel System	TM50
Fuel Type	Ultra-Low Sulfur Diesel
Fuel Capacity: gal	71
Containment:	110%
Consumption @ 75% Load: gal/hr	2.17
Consumption @ 100% Load: gal/hr	2.89

DEF	
DEF Capacity: gal	N/A

Sound Level	
23 Feet: dBA	69

Output Connections	
20A 120V Receptacles	2
50A 120-240V Receptacles	3
Cam-Lok Sets	1

