THE CONNER GROUP

AUGERS / BUCKETS / HD DRILLS / SPLICING / COW

WOMEN OWNED
UTILITY BUSINESS

EQUIPMENT SALES

TAYLOR TM170 GENERATOR

132 kW SOURCE TABLE REFERENCE | TRAILER-MOUNTED DIESEL GENERATOR



POWER & PERFORMANCE

ENGINE
FPT NEF67

FUEL CAPACITY
232 gallons

FREQUENCY
60 Hz

ENGINE SPEED
1,800 RPM

PORTABLE DIESEL POWER. READY FOR THE JOBSITE.

Trailer-mounted power with a turbocharged, EPA Tier 4 Final diesel engine.
Multiple voltage options, integral fuel tank and convenient output connections.

PACKAGE HIGHLIGHTS

- Leroy Somer LSA 44.3L12 alternator
- D350 regulator; ±0.25% regulation
- Cellular gateway for remote monitoring
- DeepSea 7310 controller
- External fuel tank connections
- Cam-Lok and busbar output connections

OUTPUT POWER OPTIONS

Genset	Voltage	Alternator	Model	Phase	Reg.	Regulation	Hz	kW/kVA	Amps
TM170	277/480	Leroy Somer	LSA 44.3L12	3	D350	±0.25%	60	132/165	199
	120/208		LSA 44.3L12	3	D350	±0.25%	60	132/165	459
	120/240		LSA 44.3L12	3	D350	±0.25%	60	132/165	397
	120/240		LSA 44.3L12	1	D350	±0.25%	60	120/120	500

Output ratings reproduced from the supplied specification sheet.

CALL FOR PRICE

Specifications/options vary; confirm quoted configuration.

TECHNICAL SPECIFICATIONS & COMPONENT DETAILS

Taylor TM170 | Specifications reproduced from the supplied equipment sheet.

ENGINE DATA

Engine data	TM170	TM225
Manufacturer	FPT	FPT
Model	NEF67	NEF67
EPA tier	4 Final	4 Final
Aspiration	Turbocharged	Turbocharged
Arrangement	Inline 6 cyl.	Inline 6 cyl.
Displacement: L (in³)	6.7 (408.859)	6.7 (408.859)
Gross horsepower	224	299
Rated RPM	1,800	1,800
Block heater wattage	1,000	1,000

DIMENSIONS & WEIGHT

Specification	TM170	TM225
Length: in.	248	248
Width: in.	87	87
Height: in.	109	109
Wet weight: lb	10,434	10,654

FUEL SYSTEM

Specification	TM170	TM225
Fuel type	Ultra-low sulfur diesel	Ultra-low sulfur diesel
Fuel capacity: gal	232	232
Containment	110%	110%
Consumption @ 75%: gal/hr	6.98	9.09
Consumption @ 100%: gal/hr	9.31	12.13

DEF

Specification	TM170	TM225
DEF capacity: gal	20	20

SOUND LEVEL

Measurement	TM170	TM225
At 23 ft: dBA	70	70

OUTPUT CONNECTIONS

Connection	TM170	TM225
20A 120V receptacles	1	1
50A 120-240V receptacles	3	2
Cam-Lok sets	1	2

