THE CONNER GROUP
AUGERS / BUCKETS / HD DRILLS / SPLICING / COW

WOMEN OWNED
UTILITY BUSINESS

EQUIPMENT SALES

WESTINGHOUSE WGen9500DF

9.5 kW DUAL-FUEL GENERATOR | REMOTE START | BACKUP POWER



POWER & PERFORMANCE

ENGINE
457cc 4-stroke OHV

FUEL CAPACITY
6.6 gallons

AC OUTPUT
120/240 V | 60 Hz

FUEL OPTIONS
Gasoline / Propane

PACKAGE HIGHLIGHTS

Starting: Remote key fob, push-button electric start and recoil backup.
Runtime: Up to 12 hours at 25% load on gasoline.
Portability: Never-flat wheels and handle; 211 lb. dry weight.
Dimensions: 27.2 in. L x 26.1 in. W x 26.5 in. H.

OUTPUT POWER OPTIONS

Fuel	Running watts	Peak watts	AC output
Gasoline	9,500 W	12,500 W	120/240 V | 60 Hz
Propane (LPG)	8,500 W	11,200 W	120/240 V | 60 Hz

Outlets: Four 120V 20A household receptacles (two GFCI duplexes), one 120/240V 30A L14-30R and one 120/240V 50A 14-50R.
Features: Automatic choke, low-oil shutdown, overload protection and fuel gauge. VFT meter displays voltage, frequency and lifetime operating hours.
CO sensor: Not equipped with automatic carbon-monoxide shutdown.

SAFE OPERATION: Use outdoors at least 20 ft. from doors, windows and vents, with exhaust directed away. Keep dry; never use indoors or in a garage. Use working CO alarms. Home connections require a properly installed transfer switch or approved interlock; never backfeed an outlet.

Source: Westinghouse manufacturer specifications. Runtime varies with load and conditions.

CALL FOR PRICE

Specifications/options vary; confirm quoted configuration.