GLADIATOR G10 HORIZONTAL DIRECTIONAL DRILL

NEW EQUIPMENT SALES | UNDERGROUND CONSTRUCTION



DRILL PERFORMANCE

THRUST / PULLBACK
11,240 lbf

ROTARY TORQUE
1,659 lb-ft

ENGINE
59 hp Yanmar diesel

FLUID SYSTEM
20 US gpm @ 870 psi max

TECHNICAL SPECIFICATIONS

Pullback Speed	226 ft/min (no load)
Rotation	250 rpm
Entry Angle	14-20 degrees
Suggested Crossing	Up to 328 ft
Suggested Reaming	Up to 15.75 in
Rod Rack	48 rods
Rod Size	1.65 in x 71.85 in
Weight	9,766 lb

EQUIPMENT & SYSTEMS

CONSTRUCTION
Manual rod loading; Yanmar 4TNV98C-PLYS diesel

CARRIAGE SYSTEM
Dual rack and pinion

SYSTEMS
Thread lubrication, front/rear clamps; adjustable mud flow

SAFETY
Strike alert/anti-shock, remote rotation lockout, emergency stops

CONTROLS
Dual joysticks; automatic drilling; wired travel control

DIMENSIONS: 175.20 in L x 59.06 in W x 62.60 in H

Current OEM G10: manual rod loading. G10L is a separate loader-equipped configuration.

EQUIPMENT SALES

Confirm configuration, availability and delivery with quotation.

CALL FOR PRICE