GLADIATOR G20 HORIZONTAL DIRECTIONAL DRILL

NEW EQUIPMENT SALES | UNDERGROUND CONSTRUCTION



DRILL PERFORMANCE

THRUST / PULLBACK
20,233 lbf

ROTARY TORQUE
2,176 lb-ft

ENGINE
72 hp Yanmar

FLUID SYSTEM
25 US gpm @ 1,080 psi max

TECHNICAL SPECIFICATIONS

Pullback Speed	200 ft/min
Rotation	223 rpm
Entry Angle	20°
Suggested Crossing	Up to 450 ft
Suggested Reaming	Up to 15.74 in
Rod Rack	40 rods
Rod Size	2.06 in × 120 in
Weight	8,998 lb

EQUIPMENT & SYSTEMS

CONSTRUCTION
Steel hood; rod-loader arms

CARRIAGE SYSTEM
Dual Rack & Pinion

SYSTEMS
Auto anchor, mud-flow adjustment, shut-off valves

SAFETY
Antifreeze tank, strike alert, seat sensor

CONTROLS
Wireless remote with hydraulic lockout shut-off

DIMENSIONS: 166.14 in L × 57.48 in W × 62.59 in H

Current OEM reference: gladiatorhdd.com/products/gladiator-g20 | Ground conditions apply.

EQUIPMENT SALES

Confirm configuration, availability and delivery with quotation.

CALL FOR PRICE