GLADIATOR G30 HORIZONTAL DIRECTIONAL DRILL

NEW EQUIPMENT SALES | UNDERGROUND CONSTRUCTION



DRILL PERFORMANCE

THRUST / PULLBACK
29,380 lb

ROTARY TORQUE
4,052 ft-lb

ENGINE
147 hp Cummins

FLUID SYSTEM
80 US gpm @ 1,080 psi max

TECHNICAL SPECIFICATIONS

Pullback Speed	209 ft/min
Rotation	234 rpm
Entry Angle	20°
Suggested Crossing	Up to 656 ft
Suggested Reaming	Up to 27.56 in
Rod Rack	65-rod onboard rack
Rod Size	2.36 in × 118.11 in
Weight	18,740 lb

EQUIPMENT & SYSTEMS

CONSTRUCTION
Steel hood; rotating cab; rod-loader arms

CARRIAGE SYSTEM
Dual rack-and-pinion

SYSTEMS
Auto anchor, mud-flow adjustment, shut-off valves

SAFETY
Antifreeze tank, strike alert, seat sensor

CONTROLS
Wireless remote with hydraulic lockout shut-off

DIMENSIONS: 227.55 in L × 84.25 in W × 93.70 in H

Current OEM G30 configuration. Earlier S/N ending 1001-1004: 52 US gpm. Ground conditions apply.

EQUIPMENT SALES

Confirm configuration, availability and delivery with quotation.

CALL FOR PRICE