GLADIATOR G40 HORIZONTAL DIRECTIONAL DRILL

NEW EQUIPMENT SALES | UNDERGROUND CONSTRUCTION



DRILL PERFORMANCE

THRUST / PULLBACK
40,465 lb

ROTARY TORQUE
5,963 ft-lb

ENGINE
167 hp Cummins

FLUID SYSTEM
66 gpm @ 1,080 psi

TECHNICAL SPECIFICATIONS

Pullback Speed	164 ft/min
Rotation	220 rpm
Entry Angle	21°
Suggested Crossing	Up to 984 ft
Suggested Reaming	Up to 31.49 in
Rod Rack	40-rod onboard rack
Rod Size	2.87/2.36 × 118.11 in
Weight	21,605 lb

EQUIPMENT & SYSTEMS

CONSTRUCTION
Steel hood, rotating cab, rod-loader arms

CARRIAGE SYSTEM
Dual rack-and-pinion

SYSTEMS
Auto anchor, mud-flow adjustment, shut-off valves

SAFETY
Antifreeze tank, strike alert, seat sensor

CONTROLS
Wireless remote with hydraulic lockout shut-off

DIMENSIONS: 267.7 in L × 89 in W × 93.7 in H

Suggested crossing and reaming figures depend on ground conditions and configuration.

EQUIPMENT SALES

Confirm configuration, availability and delivery with quotation.

CALL FOR PRICE