GLADIATOR G130 HORIZONTAL DIRECTIONAL DRILL

NEW EQUIPMENT SALES | UNDERGROUND CONSTRUCTION



DRILL PERFORMANCE

THRUST / PULLBACK
134,885 lb

ROTARY TORQUE
15,488 ft-lb

ENGINE
280 hp Cummins

FLUID SYSTEM
264 gpm @ 1,160 psi

TECHNICAL SPECIFICATIONS

Pullback Speed	213.25 ft/min
Rotation	192 rpm
Entry Angle	21°
Suggested Crossing	Up to 2,624 ft
Suggested Reaming	Up to 47.24 in
Rod Rack	24-rod onboard rack
Rod Size	3.50 × 240 in
Weight	46,297 lb

DIMENSIONS: 354 in L × 99 in W × 103 in H

Suggested crossing and reaming figures depend on ground conditions and configuration.

EQUIPMENT & SYSTEMS

CONSTRUCTION
Steel hood, rod rack with loader arms

SYSTEMS
Auto anchor, mud-flow adjustment, auto greaser

SAFETY
Antifreeze tank, strike alert, seat sensor

CONTROLS
Wireless remote with hydraulic lockout shut-off

THREE SPEED
Low, medium, high

EQUIPMENT SALES

Confirm configuration, availability and delivery with quotation.

CALL FOR PRICE