THE CONNER GROUP

60-FT INSULATED

BUCKET TRUCK

AVAILABLE NATIONWIDE

WORKING HEIGHT	PLATFORM CAPACITY	MAX. JIB CAPACITY	DRIVE
60 ft 3 in	700 lb	2,000 lb	4x4



AERIAL LIFT PACKAGE

BUCKET	Two-person 24 x 48 x 42-in fiberglass bucket
BUCKET ACCESS	Liner, cover and two access steps
AERIAL LIFT	Insulated non-overcenter articulated lift
ROTATION	Continuous; 90-degree bucket rotation
JIB	6.5-ft hydraulic articulating / extending jib

BODY & SUPPORT PACKAGE

OUTRIGGERS	Dual A-frame; 158-in spread
INTERLOCKS	Outrigger / boom and park-brake
CONTROLS	Upper and lower; engine start / stop
HYDRAULICS	Tool outlets; 12V backup pump
BODY	156-in line body; hot-stick storage

INTERNATIONAL HV507 | VERSALIFT VN-555-MHI

4x4 | Cummins B6.7 diesel, 325 hp | Allison 3500 RDS automatic
33,000-lb GVWR | Air brakes | A/C

Rental availability and rates: contact THE CONNER GROUP.

VERSALIFT VN-555-MHI

AERIAL LIFT, BODY & CHASSIS

AERIAL LIFT & MATERIAL HANDLING

WORKING / PLATFORM HEIGHT	60 ft 3 in / 55 ft 3 in (unit-specific specification)
HORIZONTAL REACH	42.8 ft (manufacturer model literature)
PLATFORM	Two-person, 24 x 48 x 42 in; 700-lb capacity
JIB / WINCH	6.5 ft; hydraulic articulation and extension; 2,000-lb max.
LOAD LINE	75 ft of 9/16-in synthetic line
LOWER-BOOM LIFTING EYE	2,500-lb maximum capacity
ROTATION / PLATFORM MOVEMENT	Continuous turret rotation; 90-degree rotation; hydraulic tilt
BOOM ARTICULATION	Lower: 120 degrees; upper: 192 degrees relative to lower
INSULATION	Category C, 46 kV and below; lower insert: 18-in gap
CONTROLS / PROTECTION	UNITROL single-stick; TruGuard dielectric isolating system
EMERGENCY FUNCTIONS	Turret control override; emergency stop; 12V backup pump

HYDRAULICS, BODY & CHASSIS

HYDRAULIC SYSTEM	Open center; 3,000 psi; 8-12 gpm; 30-gal reservoir
PLATFORM TOOL OUTLETS	Two sets with 2,000-psi reducing valve
OUTRIGGERS	Dual A-frame; 158-in spread; boom interlock
LINE BODY	156 x 54 x 94 in; locking compartments and shelves
STORAGE / ACCESS	Material hooks; 156-in hot-stick compartment; access steps
CHASSIS / POWERTRAIN	International HV507 4x4; Cummins B6.7, 325 hp
TRANSMISSION / BRAKES	Allison 3500 RDS automatic; air brakes
GVWR / AXLE RATINGS	33,000 lb; front 13,000 lb; rear 21,000 lb
EQUIPMENT	Pintle hitch; trailer connector; strobes; grounding system

Specifications reflect supplied unit documents. Model literature lists 60 ft 6 in working height; this sheet uses the unit-specific 60 ft 3 in. Capacities depend on configuration and load chart.