THE CONNER GROUP

WOMEN-OWNED UTILITY BUSINESS

RPO EQUIPMENT

GLADIATOR G10

HORIZONTAL DIRECTIONAL DRILL | RENTAL PURCHASE OPTION



Manufacturer-supplied model photograph. Equipment configuration confirmed on quotation.

CONFIGURATION AT A GLANCE

THRUST / PULLBACK
11,240 lb

ROTARY TORQUE
1,659 ft-lb

ENGINE
59 hp Yanmar

FLUID SYSTEM
20 gpm @ 870 psi

SUPPLIED CONFIGURATION SPECIFICATIONS

Pullback speed: 200 ft/min
Rotation: 215 rpm
Entry angle: 20 degrees
Suggested crossing: Up to 328 ft
Suggested reaming: Up to 15.74 in
Rod rack: 48 rods
Rod size: 1.65 in x 71.85 in
Weight: 8,157 lb
Dimensions: 166.14 L x 57.48 W x 62.59 H in

CONSTRUCTION
Steel hood; optional rod-loader arms

SYSTEMS
Auto anchor, mud-flow adjustment, shut-off valves

SAFETY
Antifreeze tank, strike alert, seat sensor

CONTROLS
Wireless remote with hydraulic lockout shut-off

Specifications reflect the supplied TCG brochure configuration. Suggested crossing and reaming are guidance, not performance guarantees. Confirm configuration and RPO terms on quotation.

RENTAL PURCHASE OPTION (RPO)

Ask for model-specific RPO terms, configuration and availability.

CALL FOR PRICE