THE CONNER GROUP

WOMEN-OWNED UTILITY BUSINESS

RPO EQUIPMENT

GLADIATOR G20

HORIZONTAL DIRECTIONAL DRILL | RENTAL PURCHASE OPTION



Manufacturer-supplied model photograph. Equipment configuration confirmed on quotation.

CONFIGURATION AT A GLANCE

ENGINE
72 hp Yanmar

FLUID FLOW
30 gpm

PULLBACK SPEED
200 ft/min

ROTATION
223 rpm

SUPPLIED CONFIGURATION SPECIFICATIONS

Pullback speed: 200 ft/min
Rotation: 223 rpm
Entry angle: 20 degrees
Suggested crossing: Up to 450 ft
Suggested reaming: Up to 15.74 in
Rod size: 2.06 in x 120 in
Weight: 8,998 lb
Dimensions: 166.14 L x 57.48 W x 62.59 H in

CONSTRUCTION
Steel hood; rod-loader arms

SYSTEMS
Auto anchor, mud-flow adjustment, shut-off valves

SAFETY
Antifreeze tank, strike alert, seat sensor

CONTROLS
Wireless remote with hydraulic lockout shut-off

Thrust, torque, rod-rack capacity and fluid pressure are omitted pending configuration verification. Other specifications reflect the supplied TCG brochure; confirm all quoted specifications before commitment.

RENTAL PURCHASE OPTION (RPO)

Ask for model-specific RPO terms, configuration and availability.

CALL FOR PRICE