THE CONNER GROUP

WOMEN-OWNED UTILITY BUSINESS

RPO EQUIPMENT

GLADIATOR G60

HORIZONTAL DIRECTIONAL DRILL | RENTAL PURCHASE OPTION



Manufacturer-supplied model photograph. Equipment configuration confirmed on quotation.

CONFIGURATION AT A GLANCE

THRUST / PULLBACK
62,946 lb

ROTARY TORQUE
9,219 ft-lb

ENGINE
202 hp Cummins

FLUID SYSTEM
125 gpm @ 1,080 psi

SUPPLIED CONFIGURATION SPECIFICATIONS

Pullback speed: 213 ft/min
Rotation: 220 rpm
Entry angle: 21 degrees
Suggested crossing: Up to 1,312 ft
Suggested reaming: Up to 39.37 in
Rod rack: 36 rods
Rod size: 2.87 in x 118.11 in
Weight: 25,353 lb
Dimensions: 283.46 L x 89.37 W x 94.48 H in

CONSTRUCTION
Steel hood; rotating cab; rod-loader arms

CARRIAGE
Dual rack-and-pinion

SYSTEMS
Auto anchor, mud-flow adjustment, shut-off valves

SAFETY
Antifreeze tank, strike alert, seat sensor

CONTROLS
Wireless remote with hydraulic lockout shut-off

Specifications reflect the supplied TCG brochure configuration. Suggested crossing and reaming are guidance, not performance guarantees. Confirm configuration and RPO terms on quotation.

RENTAL PURCHASE OPTION (RPO)

Ask for model-specific RPO terms, configuration and availability.

CALL FOR PRICE