THE CONNER GROUP

WOMEN-OWNED UTILITY BUSINESS

RPO EQUIPMENT

GLADIATOR G100

HORIZONTAL DIRECTIONAL DRILL | RENTAL PURCHASE OPTION



Manufacturer's G100 listing photo shows G100A variant; exact configuration subject to confirmation.

CONFIGURATION AT A GLANCE

THRUST / PULLBACK
100,838 lb

ROTARY TORQUE
14,013 ft-lb

ENGINE
260 hp Cummins

FLUID SYSTEM
175 gpm @ 1,160 psi

SUPPLIED CONFIGURATION SPECIFICATIONS

Pullback speed: 213.25 ft/min
Rotation: 192 rpm
Entry angle: 21 degrees
Suggested crossing: Up to 2,624 ft
Suggested reaming: Up to 47.24 in
Rod rack: 12 rods
Rod size: 3.50 in x 181.1 in
Weight: 46,297 lb
Dimensions: 354 L x 99 W x 103 H in

CONSTRUCTION
Steel hood; 20-ft rod rack with loader arms

SYSTEMS
Auto anchor, mud-flow adjustment, shut-off valves

SAFETY
Antifreeze tank, strike alert, seat sensor

CONTROLS
Wireless remote with hydraulic lockout shut-off

Specifications reflect the supplied TCG brochure configuration. Suggested crossing and reaming are guidance, not performance guarantees. Confirm configuration and RPO terms on quotation.

RENTAL PURCHASE OPTION (RPO)

Ask for model-specific RPO terms, configuration and availability.

CALL FOR PRICE