THE CONNER GROUP

57 FT MATERIAL HANDLER

DUR-A-LIFT DPM-52

MH / DU CONFIGURATIONS

WORKING HEIGHT	SIDE REACH	BASKET WITH JIB	JIB CAPACITY
57 ft	31 ft 6 in	400 lb	Up to 1,000 lb



DPM-52MH shown; chassis and installed options vary.







BASKET & AERIAL OPTIONS

MH: single-person material handling.
DU: two-person personnel or single-person material handling. Aluminum or fiberglass.
Options: outriggers, liner, tool circuits, D.C. backup, high-resistance controls.
DPM: insulated; DPMS: non-insulated.
Confirm insulation and basket rotation for the supplied unit before rental.

AERIAL & CONFIGURATION SPECIFICATIONS

Platform height	52 ft to bottom of platform
MH basket	24 x 30 in; 400 lb
DU basket	24 x 42 in; 400 lb with jib
DU without jib	550 lb; personnel mode
Approx. travel height	11 ft 8 in stowed
Approx. lift weight	4,400 lb
Articulating arm travel	0 to 75 degrees
Main boom travel	-30 to 75 degrees
Extension travel	120 in
Minimum chassis	22,000 lb GVWR; 108 in cab-to-axle
Rotation / leveling	Continuous aerial / hydraulic basket
Controls	Proportional; lower override

Capacities are configuration-dependent. Follow the supplied unit load chart and operating manual.
Source: dur-a-lift.com/products/dpm-mh-du-series/ and manufacturer DPM series literature.