THE CONNER GROUP

TRAILER MOUNTED BUCKET

INSULATED / NON-INSULATED

HEIGHT - SOURCE TITLE	BUCKET CAPACITY	POWER SUPPLY	ROTATION
25-46 ft	300 lb	12 Volt DC	720 degrees







Working-height source table states 24-46 ft; source title states 25-46 ft. Confirm configuration.

BUCKET & HYDRAULIC SYSTEM

Bucket	Side-hung; walk-through aluminum / fiberglass bucket with door and switch pod
Configurations	Telescoping or articulating units available
Hydraulics	Two-speed hydraulic operation with hydraulic bucket leveling
Pump / motor	12 Volt DC heavy duty with dual pumps and motors
Power supply	12 Volt deep-cycle battery supplies power to the electric pump and motor
Outriggers	Outrigger pads provided; manual jacks for side-mount outriggers
Emergency bleed	Manual emergency bleed-down at the bucket

CONTROLS & STANDARD EQUIPMENT

Controls	Upper and lower controls with override; upper controls in bucket for safe operation
Safety	Safety harness and shock lanyard
Finish	Bright white with safety scotch lite yellow stripe
Rotation	720-degree non-continuous with stop; completely enclosed in oil bath; maintenance- and adjustment-free
Cylinders	Counterbalance valve on all cylinders prevents creep and locks cylinders if a hydraulic line fails
Documentation	Two operator's and service manuals
Compliance	Meets or exceeds all OSHA and ANSI 92.2 requirements

chris@tcgequip.com